

Wireless handsets for teams on the go

# DECT IP Handsets



## On-site wireless communications

Today's business environment demands flexible ways of working and excellent customer service. Organisations seek to extend the reach of their converged voice and data network and integrate wireless communications without compromising on voice quality, availability and security. NEC's Business Mobility IP DECT realises all of this, and much more.



### High quality audio experience

DECT compliance ensures high quality audio and security with seamless mobility.



### Flexibility with Bluetooth

Wired and Bluetooth\* headset support.



### Directories

Unified communications features including central directory access.



### Keep your staff safe

SOS, Man down, messaging and location services for staff security.\*



### All the power, all the time

Dual chargers, rack chargers and the ability to charge additional batteries.



### Easy to keep in touch

Easy to use and intuitive phones make staying in contact easy.



G277



G577



G577H



1766

\* Only available on selected models

## NEC DECT IP Wireless Handset Range

Model	G277	G577	G577H	I766
-------	------	------	-------	------

### General Specifications

Colour	Black	Black	White	Silver / Black
Dimensions	128 x 49 x 21 mm	128 x 49 x 21 mm		145 x 55 x 24 mm
Weight	130g	144g		181g
Standby time	Up to 160 hours	Up to 160 hours		Up to 160 hours
Talk time	Up to 20 hours	Up to 20 hours		Up to 16 hours
Antibacterial provisions	-	-	✓	-
Multi-line	-	✓		✓
Programmable keys	-	4 keys		4 keys
Memory card for handset settings	MicroSD	MicroSD		MicroSD
Personal directory	200	200		200
Central directory	✓	✓		✓
OTA software downloads	✓	✓		✓
IP-class	IP40	IP65		IP65

### Charging

Charger	Dual	Dual		Dual
Multi-charger rack	✓	✓		✓
Handsets per rack	6	6		6

### Display

Screen	1.77" colour	2.0" colour		2.2" colour
Resolution	162 x 62 (dots)	240 x 320 (dots)		320 x 240px

### Call Handling and Audio

Auto answer	✓	✓		✓
Calling name display	✓	✓		✓
Calling line (CLIP)	24 digits	24 digits		24 digits
Call logging	50 entries	50 entries		50 entries
CAT-iq - HD audio	✓	✓		✓

## NEC DECT IP Wireless Handset Range

Model	G277	G577	G577H	I766
Audio connector	USB-C (Analogue)	USB-C (Analogue)	USB-C (Analogue)	3.5mm
Bluetooth	-	✓	✓	✓
Speakerphone	✓	✓ (HD Audio)	✓ (HD Audio)	✓ (HD Audio)

### Location and Safety

RSSI	✓	✓	✓	✓
Beacon	-	-	-	DLA
Man down alarm	-	-	-	✓
Pull cord alarm	-	-	-	✓
Messaging	-	✓	✓	✓
SOS button	-	✓	✓	✓
Trembler alarm	✓	✓	✓	✓

## For more information:

 [nec.com.au](http://nec.com.au)

 [contactus@nec.com.au](mailto:contactus@nec.com.au)

 131 632

**Corporate Headquarters (Japan)**  
NEC Corporation  
[www.nec.com](http://www.nec.com)

**Australia**  
NEC Australia Pty Ltd  
[www.nec.com.au](http://www.nec.com.au)

**North America (USA)**  
NEC Corporation of America  
[www.necam.com](http://www.necam.com)

**Asia Pacific (AP)**  
NEC Asia Pacific  
[www.sg.nec.com](http://www.sg.nec.com)

**Europe (EMEA)**  
NEC Enterprise Solutions  
[www.nec-enterprise.com](http://www.nec-enterprise.com)

v.19.12.12 | DECT IP Wireless Handsets

NEC Australia Pty Ltd reserves the right to change product specifications, functions, or features, at any time, without notice. Please refer to your local NEC representatives for further details. Although all efforts have been made to ensure that the contents are correct, NEC shall not be liable for any direct, indirect, consequential or incidental damages resulting from the use of the equipment, manual or any related materials. The information contained herein is the property of NEC Australia Pty Ltd and shall not be reproduced without prior written approval from NEC Australia Pty Ltd.

©2019 NEC Australia Pty Ltd. All rights reserved. NEC and NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All other trademarks are the property of their respective owners. All rights reserved. Printed in Australia. Note: This disclaimer also applies to all related documents previously published.

**NEC**